



BRAND

Juno Lighting

DESCRIPTION

5 Inch 120 Volt 600 Lumen Generation 4 LED IC Remodel Housing is a dedicated LED, Air-Loc sealed remodel housing with integral light engine. Shallow housing allows for fit in 2 x 6 construction. IC remodel housing can be completely covered with insulation. For remodel applications where back side of ceiling is not accessible. Installs through an opening in the ceiling from below. Fully sealed housing stops infiltration and exfiltration of air reducing heating and air cooling costs without the use of additional gaskets. Replaceable light engine mounts directly to housing and incorporates the latest generation high lumen output LED array. Comparable light output to 65 watt BR30 incandescent while consuming less than 11.5 watts. Available with 2700K, 3000K, 3500K, or 4100K color temperature, 90 minimum CRI. Wide flood distribution shipped as standard. Optional optic accessories available, sold separately. 120 volt only driver is dimmable with the use of most incandescent, magnetic low voltage and electronic low voltage wall box dimmers (see attached manufacturer dimmer compatibility reference). Life rated for 50,000 hours at 70 percent lumen maintenance. Energy Star. Title 24 compliant with select trims. UL listed for damp locations. 13.5 inch length x 5.9 inch width x 4.9 inch height. A complete fixture includes a housing and trim, sold separately.





Shown in: Aluminum

TRIM COLOR	N/A
BODY FINISH	Aluminum
WATTAGE	11.5W
DIMMER	Dimmable
DIMENSIONS	13.5"L x 5.9"W x 4.9"H
INTEGRATED LED MODULE	
LAMP	1 x LED/120V LED

Technical Information

LUMINOUS FLUX	600 lumens
LUMENS/WATT	52.17
LAMP COLOR	2700K
COLOR RENDERING	90 CRI
BEAM ANGLE	50000°
CEILING TYPE	Drywall with Trim
HOUSING TYPE	Remodel IC

SPEC # JUN110995



5 1/2" CEILING CUTOUT

COMPANY

PROJECT

FIXTURE TYPE

APPROVED BY

DATE