



BRAND

PureEdge Lighting

DESCRIPTION

SS1 Soft Strip provides accent light with (VW) 2700K Very Warm White, 73 lumens per watt/102 lumens per foot. 80+ CRI LED, or (WW) 3000K Warm White, 88 lumens per watt/123 lumens per foot, 80+CRI LED. 32,000 hour average lamp life. At less than .38 inches wide the flexible copper strip features an optically clear protective coating. Includes easy plug in connectors on each end and a 6 foot power feed cable. Use plug in flexible connectors for making turns and custom configurations. Self adhering SS1 mounts to most smooth finished surfaces with industrial strength 3M tape provided on back of strip. Some unfinished surfaces may require screw in mounting clips, sold separately. Includes a flexible aluminum heat sink to extend LED life. 0-10 power supplies include a 24 volt 96, 2X96, 3X96, or 4X96 watt power supply, dimmable with a 0-10 volt dimmer (tested and approved Philips Sunrise SR1200ZTUNV), sold separately. ELV power supplies include a 24 volt 60, 100, 2X100, 3X100 or 4X100 watt power supply, dimmable with a low voltage electronic dimmer (tested and approved: Legrand Adorne ADTP703TU, Lutron DIVA DVELV-300P, Lutron Skylark SELV-300P, Lutron Maestro MAELV-600, or Lutron Radio Ra 2), sold separately. Designed for indoor open air environments. ETL listed to conform to UL 2108 for closet and under-cabinet applications. Fixture includes a 5 year warranty. Limited quantities available.



SHADE COLOR	N/A
BODY FINISH	Aluminum
WATTAGE	2W
DIMMER	Dimmable
DIMENSIONS	12"L x 0.375"W
INTEGRATED LED MODULE	
LAMP	LED/2W/24V LED

Technical Information

LUMINOUS FLUX	102 lumens
LUMENS/WATT	51.00
LAMP COLOR	2700K
COLOR RENDERING	80 CRI

SPEC # EDG121396

COMPANY	PROJECT	FIXTURE TYPE	APPROVED BY	DATE