

Light Channel Surface 2.3W 24V Dry SPEC # EDG121652



DESIGNERGregory KayBRANDPureEdge Lighting

DESCRIPTION

Surface Mount Dry Location Light Channel features 24 volt Soft Strip inside a slim, paintable aluminum extrusion. LCSM includes 2.3 watts per foot premium grade LED Soft Strip with 3000K Warm White, 80+CRI LEDs for excellent color-rendering. 37 lumens per watt/115 lumens per foot. 50,000 hour average lamp life. The white diffuser lens projects a clean line of light and eliminates LED dots, while the clear lens provides maximum light levels. Available in various sizes up to 120 inches. Fixtures include LC-MCL mounting clips every 2 feet and can be linked end-to-end with plug-in or flexible connectors to a maximum of 40 feet. System is powered by a dimmable electronic low voltage or 0-10V remote power supply. ELV power supplies include a 60, 100, 2X100, 3X100 or 4X100 watt option, dimmable with Legrand Adorne ADTP703TU, Lutron Diva DVELV-300P, Lutron Skylark SELV-300P, Lutron Maestro MAELV-600, or Lutron Radio Ra 2. 0-10V power supplies include a 96, 2X96, 3X96 or 4X96 watt option, dimmable with Philips Sunrise SR1200ZTUNV. ETL listed. Major components made and assembled in the USA. 5 year warranty. Required power supply, dimmer control and optional accessories sold separately. Product is built to order.

SHADE COLOR	Diffused Lens
BODY FINISH	Satin Aluminum
WATTAGE	1W
DIMMER	Dimmable
DIMENSIONS	3"L x 0.68"H x 0.8"D
INTEGRATED LED MODULE	
LAMP	LED/1W/24V LED
Technical Information	
LUMINOUS FLUX	37 lumens
LUMENS/WATT	37.00
LAMP COLOR	3000K
COLOR RENDERING	80 CRI
SPEC #	EDG121652



COMPANY	PROJECT	FIXTURE TYPE	APPROVED BY	DATE