

Light Channel Surface 2.5W 24V Wet



Designer: Gregory Kay

Description:

Surface Mount Wet Location Light Channel features 24 volt Soft Strip inside a slim, paintable aluminum extrusion. LCSMC includes 2.5 watts per foot commercial grade SS2C LED Soft Strip with (VW) 2700K or (WW) 3000K, 95CRI, or (AW) 2400K, (NW) 3500K, (CW) 4000K, or (DW) 5700K color temperature, 85CRI. 43 lumens per watt/126 lumens per foot. 50,000 hour lamp life. The white diffuser lens projects a clean line of light and eliminates LED dots, while the clear lens provides maximum light levels. Available in various sizes up to 120 inches. Fixtures include LC-MCL mounting clips every 2 feet and can be linked end-to-end with plug-in or flexible connectors to a maximum of 40 feet. System is powered by a dimmable electronic low voltage or 0-10V remote power supply. ELV power supplies include a 60, 100, 2X100, 3X100 or 4X100 watt option, dimmable with Legrand Adorne ADTP703TU, Lutron Diva DVELV-300P, Lutron Skylark SELV-300P, Lutron Maestro MAELV-600, or Lutron Radio Ra 2. 0-10V power supplies include a 96, 2X96, 3X96 or 4X96 watt option, dimmable with Phillips Sunrise SR1200ZTUNV. Included Components: LC-CFX Flexible Connectors, SS-CFXT Flexible T-Connector, 3RE-WH Canopy Cover and Splice Box, and LC-MCL Mounting Clips. ETL listed for wet locations. Major components made and assembled in



Shown in: Satin Aluminum / White

List Price: \$71.00
Our Price: \$56.80

Shade Color: White
Body Finish: Satin Aluminum
Lamp: 1 x LED/0.62W/24V LED
Wattage: 0.62W
Dimmer: Dimmable
Dimensions: 3"L x 0.68"H x 0.8"W

Technical Information

Luminous Flux: 43 lumens
Lumens/Watt: 69.35
Lamp Color: 2700 K
Color Rendering: 95 CRI
Lamp Life: 50000 hours



Product Number: EDG 122287			
Company:		Fixture Type:	Date: Feb 20, 2018
Project:		Approved By:	

#1200SM-LIGCDVW-003L1-XXSA

Fax: (773) 883-6131

Phone: 866-954-4489

Address: 1718 W. Fullerton Ave. Chicago IL 60614

www.Lightology.com