



DESIGNER


Gregory Kay

BRAND

PureEdge Lighting

DESCRIPTION

Micro Grazer Dry Location Light Channel features 24 volt commercial-grade 95CRI LEDs included inside a slim, paintable aluminum extrusion. The asymmetrical 10 degree lens is ideal for creating dramatic grazing effects. Sold in 12 inch increments up to 120 inches. Available in 3, 5, 8 and 10 inch increments upon request. Each foot of Light Channel contains 7 watts LED available in Very Warm White 2700K or Warm White 3000K color temperature, 95+ CRI, or Amber White 2400K, Neutral White 3500K, Cool White 4000K, or Daylight White 5700K color temperature, 85+ CRI. 50,000 hour average lamp life. Can be powered using an electronic low voltage or 0-10 power supply. 0-10 power supplies include a PSB-96W-010-24VDC, PSB-2X96-010-24VDC, PSB-3X96W-010-24VDC or PSB-4X96W-010-24VDC, dimmable with a 0-10 volt dimmer (tested and approved Philips Sunrise SRI200ZTUNV), sold separately. ELV power supplies include a PSB-60W-ELV-24VDC, PSB-100W-ELV-24VDC, PSB-2X100W-ELV-24VDC, PSB-3X100W-ELV-24VDC or PSB-4X100W-ELV-24VDC, dimmable with a low voltage electronic dimmer (tested and approved Legrand Adorne ADTP703TU, Lutron DIVA DVELV-300P, Lutron Skylark SELV-300P, Lutron Maestro MAELV-600, or Lutron Radio Ra 2), sold separately. Includes 8 foot power feed cable and mounting clips for each 2 foot section. Fixtures can be linked end to end with plug-in or flexible connectors, sold separately, for a maximum of 12 feet. Fixture includes a 5 year warranty. ETL listed for dry locations. Major components made and assembled in the USA. Required power supply and optional dimmer and mounting accessories, sold separately.



SHADE COLOR	N/A
BODY FINISH	Satin Aluminum
WATTAGE	1.8W
DIMMER	Dimmable
DIMENSIONS	3"L x 0.8"W x 0.79"H
INTEGRATED LED MODULE	
LAMP	1 x LED/1.8W/24V LED

Technical Information

LUMINOUS FLUX	90 lumens
LUMENS/WATT	50.00
LAMP COLOR	2700K
COLOR RENDERING	95 CRI

SPEC # EDG125686



COMPANY

PROJECT

FIXTURE TYPE

APPROVED BY

DATE