



### DESIGNER

Gregory Kay

### BRAND

PureEdge Lighting

### DESCRIPTION

Cirrus Ceiling Channel Lensed Wet Location Wall Grazer features a lens that provides dramatic accent lighting to highlight textured surfaces. At 7 watts LED per foot, the 24 volt DC channel is available in 2200K, 3500K, 4000K or 5700K, 85+CRI, or 2700K or 3000K, 95+CRI. 50,000 hour average lamp life. Finish available in Satin Aluminum, Chrome, Satin Nickel, Antique Bronze, Satin Black or White. Wet location option sold in 12 inch increments up to 120 inches. May be ordered in 3, 5, 8 and 10 inch increments upon request. See attached manufacturer specification for actual lengths. Channel includes a split canopy that mounts on a standard junction box. May be ordered with a Slim Profile Junction Box (C-1RE-JBOX), sold separately. Mounting clips (C-MCL) are provided every 18 inches. Can be powered with a Class 2 0-10 volt or electronic low voltage power supply. 0-10 power supplies include a 24VDC 25, 96, 2X96, 3X96 or 4X96 watt option, dimmable with a 0-10 volt dimmer (tested and approved Philips Sunrise SR1200ZTUNV). ELV power supplies include a 24VDC 40, 60, 100, 2X100, 3X100 or 4X100 watt option, dimmable with a low voltage electronic dimmer (tested and approved Legrand Adorne ADTP703TU, Lutron DIVA DVELV-300P, Lutron Skylark SELV-300P, Lutron Maestro MAELV-600 and Lutron Radio Ra 2). ETL listed. IP64 rated for covered areas in wet locations. Fixture includes a 5 year warranty. Major components made and assembled in the USA. Required power supply, dimmer control, and optional mounting accessories, sold separately. Product is built to order.




SHADE COLOR	N/A
BODY FINISH	Satin Nickel
WATTAGE	7W
DIMMER	Dimmable
DIMENSIONS	12"L x 0.9"W x 0.9"H
INTEGRATED LED MODULE	
LAMP	1 x LED/7W/24V LED

#### Technical Information

LUMINOUS FLUX	442 lumens
LUMENS/WATT	63.14
LAMP COLOR	2700K
COLOR RENDERING	95 CRI

SPEC #	EDG135187
--------	-----------



COMPANY	PROJECT	FIXTURE TYPE	APPROVED BY	DATE