



BRAND

PureEdge Lighting

DESCRIPTION

The Cirrus R1 Lens End Feed Suspension with Remote 24VDC Power Supply (sold separately) and Square Canopy is a linear LED fixture that offers direct light in a clean, contemporary style. Features a diffused white rectangular lens with a 140 degree beam spread available in various increments from 36 to 420 inches, a variety of finishes, four wattage options, and a spectrum of color temperature options. Product is built to order. Note: Canopy mounts to a standard junction box either using the PS-60L-ELV-24VDC (60 Watt 24 Volt DC Power Supply) which fits inside junction box, or from a 24VDC remote Universal (UNI) power supply. Universal dimming with UNI power supply (TRIAC/ELV/0-10V). ELV dimming with PS-60L-ELV power supply. Power supply, dimmer control, and optional accessories sold separately. Note: Includes a 4.6 inch square canopy and adjustable 12 foot coaxial and aircraft cables. Additional aircraft cables are included for support when fixture exceeds 96 inches. Lengths over 96 inches ship as two segments.



SHADE COLOR	White Lens
BODY FINISH	Satin Nickel
WATTAGE	5W
DIMMER	Dimmable
DIMENSIONS	12"L x 0.9"W x 1.46"H
INTEGRATED LED MODULE	
LAMP	1 x LED/24V LED

Technical Information

LUMINOUS FLUX	238 lumens
LUMENS/WATT	47.60
LAMP COLOR	2700K
COLOR RENDERING	95 CRI
BEAM ANGLE	100°

SPEC #	EDG152964
--------	-----------



COMPANY

PROJECT

FIXTURE TYPE

APPROVED BY

DATE