





BRAND Contrast Lighting

DESCRIPTION

ECOL3B 3.5 Inch Square Adjustable 6 Watt LED Trim features a Narrow Flood with 30 to 35 degree beam angle in Very Warm White 2700K or Warm White 3000K color temperature, 80 CRI, 61 lumens per watt for a total of 368 lumens. Available in a 6 and 10 watt option in 2700K or 3000K color temperature with narrow flood or wide flood beam angle. Provides high quality clean white light without pixilation. Finish available in White, Brushed Chrome, Matte White, Brushed Nickel, or Metallic Grey. Includes Fulham driver power supply, constant current output, 10 watt output wattage, 120 volt, THD less than 10 percent. CHIP Bridgelux LED arrays deliver a lumen maintenance greater than 70 percent after 50,000 hours of operation. Compatible housings include ECOREL300U remodel housing and ECONWL300U and ECOISL300U new construction housings. See housing specification for dimming options. cUL certified for damp locations. Available in marine grade version for high humidity, high salinity, or wet locations upon request. 4.25 inch square outside dimension x 2.5 inch height.



TRIM COLOR	N/A
BODY FINISH	White
WATTAGE	6W
DIMMER	Dimmable
DIMENSIONS	4.25"W x 2.5"H x 4.25"D
INTEGRATED LED MODULE	
LAMP	1 x LED/120V LED
Technical Information	
LAMP COLOR	2700K
COLOR RENDERING	80 CRI
BEAM SPREAD	Narrow flood
SPEC #	CLT167863



COMPANY	PROJECT	FIXTURE TYPE	APPROVED BY	DATE