

BRAND

Juno Lighting

DESCRIPTION

6 Inch New Construction LED housing with integral 3500K color temperature, 14 watt nominal light engine and universal 120V-277V. Air-Loc fully sealed housing does not require separate gasket. IC housing designed for use in IC or non-IC construction. Housing is vertically adjustable to accommodate up to a 1 inch ceiling thickness. Driver is dimmable with recommended low voltage electronic dimmers including Lutron Skylark SELV-300P and 303P, Lutron Diva DVELV-300P, and Lutron Nova T NTELV-300 and NTELV-600. Fourteen 1 watt LEDs included. Rated for 50,000 hours at 70 percent lumen maintenance. A complete fixture consists of housing and trim, both sold separately. 6.9 inch ceiling cutout. 9.1 inch width x 16.1 inch length x 7.1 inch height.



TRIM COLOR	N/A
BODY FINISH	Galvanized Steel
WATTAGE	14W
DIMMER	Dimmable
DIMENSIONS	16.1"L x 9.1"W x 7.1"H
INTEGRATED LED MODULE	
LAMP	LED/14W/120V LED

Technical Information

HOUSING TYPE	New construction NON IC Airtight
HOUSING HEIGHT	7"

SPEC # JUN184074

COMPANY	PROJECT	FIXTURE TYPE	APPROVED BY	DATE