



BRAND

RSA

DESCRIPTION

Low voltage remodel housing for Quiet Ceiling square trims. Integral low voltage magnetic transformer mounted to j-box and attached to housing via 12 inch flexible conduit. For remodel applications, for insulated ceiling applications. Insulation must be kept 3 inches from all sides and at least one inch above the housing. Mudding ring and mounting tabs adjust in plaster frame to accomodate various thickness. One 12 volt max 50 watt MR16 lamp not included. 9 inch mesh plate below ceiling. Compatible trims: QCT1876, QCT1875, QCT2275. UL listed. Ceiling cutout 7.1 inch diameter. 7.1"L x 5.2" H.



TRIM COLOR	N/A
BODY FINISH	Black
WATTAGE	50W
DIMMER	N/A
DIMENSIONS	7.1"L x 5.2"H
BULB NOT INCLUDED	
LAMP	MR16/GU5.3 (bipin)/50W/12V Halogen MR16/GU5.3 (bipin)/12V LED

Technical Information

CEILING TYPE	Drywall Trimless/Flush
HOUSING TYPE	Remodel IC
HOUSING HEIGHT	6"
APERTURE SHAPE	Square

SPEC #	RSA18771
--------	----------

COMPANY	PROJECT	FIXTURE TYPE	APPROVED BY	DATE