



BRAND

Lightolier by Signify

DESCRIPTION

Lytecaster 1100AICMFT 6.75 Inch Compact Fluorescent Insulated Ceiling AirSeal Frame-In Kit is made of galvanized steel. UL listed for direct contact with thermal insulation (IC designation). AirSeal minimizes air leakage to less than 2CFM at 1.57 PSF and reduces heat loss and condensation in ceiling. Accommodates all ceilings up to 1 inch thick. Four slots are positioned 90 degrees apart to simplify alignment. Push-in/twist-out rotoclips hold reflector flush to ceiling. UL listed for maximum of six No. 12 gauge 90 degree C through branch circuit conductors. Quick release cover for outside access to wiring. Mounting bars extend 16 to 24 inch on center joist spacing and feature integral nail or secure attachment to wood construction. Attaches to T-bar ceilings without the need of accessories. UL listed. Suitable for damp locations. Dimensions: 14.9 inch width x 9 inch depth x 6.2 inch height. Compact fluorescent lamping type and wattage dependent on trim and frame-in kit combination per attached manufacturer spec. A complete fixture consists of a frame-in kit and trim kit, sold separately.



TRIM COLOR	N/A
BODY FINISH	Galvanized Steel
WATTAGE	32W
DIMMER	Not Dimmable
DIMENSIONS	14.9"W x 6.2"H x 9"D
BULB NOT INCLUDED	
LAMP	1 x T4/GX24q-3/32W/120V Compact Fluorescent

Technical Information

CEILING TYPE	Drywall with Trim
HOUSING TYPE	New construction IC Airtight
HOUSING HEIGHT	7"

SPEC #	LTL19054
--------	----------

COMPANY	PROJECT	FIXTURE TYPE	APPROVED BY	DATE