

1102Hf 6 Inch New Construction Non Ic Housing SPEC # LTL19060

BRAND

Lightolier by Signify

DESCRIPTION

Lytecaster 7 High Intensity Discharge (HID), Universal 6 3/4 inch Aperture Frame-In Kit System in raw aluminum. Splice Box is fastened to ballast and #16 ga. ballast plate to form one complete assembly locked by retaining screw to mounting frame. Complete assembly accessible from below for inspection and replacement. $4 \times 3 \frac{1}{2} \times 2 \frac{14}{9}$ steel junction box contains plug-in connectors for ballast assembly. May be wired-in before ballast assembly is installed. Integral cable clamps permit attachment of nonmetallic romex or armored cable without need for additional connectors. Mounting frame is electro-galvanized steel, furnished with 13 inch long mounting bars. Use open fixture (no glass guard) E and ED metal halide lamps. Lamp not included. 11.125W x 9L.



TRIM COLOR
BODY FINISH
Raw
WATTAGE 100W
DIMMER Not Dimmable
DIMENSIONS 9"L x 11.125"W

BULB NOT INCLUDED

LAMP 1 x ED-17/Medium (E26)/100W/120V High Intensity Discharge

Technical Information

CEILING TYPE Drywall with Trim
HOUSING TYPE New Construction NON IC
HOUSING HEIGHT 3.5"

SPEC # LTL19060

COMPANY	PROJECT	FIXTURE TYPE	APPROVED BY	DATE