

BRAND Lightolier by Signify

DESCRIPTION

Lytecaster 7 Low Profile Compact Fluorescent Frame-In Kit in grey steel. Non-Insulated Ceiling (Non-IC), HPF 120V, accommodates all ceilings up to 1 inch thick. Low profile 3 7/8 inch depth including ceiling material and reflector trim. For ceilings thicker than 5/8 inch depth from finished ceiling will be ceiling thickness (max. 1 inch) plus 3 1/4 inch. Push-in/twist-out rotoclips hold reflector flush to ceiling. Junction box is rated for through branch circuit wires. Quick release L shaped cover for access to wiring. Integral cable clamps permit attachment of nonmetallic romex or armored cable without need of additional connectors. For mounting, four bars, 13 inch long, extend to 27 inch permit off-center mounting bars rotate 90 inch and lock in both directions integral poised nailer for wood joists, locking tabs for T-bar runners. 2 light electroma



TRIM COLOR	N/A
BODY FINISH	Galvanized Steel
WATTAGE	26W
DIMMER	Not Dimmable
DIMENSIONS	9"L x 18.25"W
BULB NOT INCLUDED	
LAMP	2 x T4/GX23-2/13W/120V Compact Fluorescent
Technical Information	
CEILING TYPE	Drywall with Trim
HOUSING TYPE	New Construction NON IC
HOUSING HEIGHT	3.5"
SPEC #	LTL19070

COMPANY	PROJECT	FIXTURE TYPE	APPROVED BY	DATE