Lightology

SPEC #

LTL19222



BRAND

Lightolier by Signify

DESCRIPTION

2000LV Lytecaster 3.75 Inch Low Voltage MR16 Non-IC Standard New Construction Frame-In Kit is made of 20 gauge galvanized steel and will accommodate existing ceilings up to 1 inch thick. Non-IC designation requires that insulation be kept a minimum of 3 inches away from housing. Includes magnetic low voltage transformer, removable from below. UL listed. Suitable for damp locations. 3 11/16 inch ceiling opening. 9 5/8 inch length x 7.5 inch width. Overall height dependent on selected trim option. Lamp type and wattage dependent on trim kit and frame-in kit combination per attached manufacturer spec sheet. A complete fixture consists of a trim kit and frame-in kit, sold separately. Dimmable with low voltage magnetic dimmer if used with a halogen MR16 lamp.



TRIM COLOR	N/A		
BODY FINISH	Galvanized Stee		
WATTAGE	50W		
DIMMER	Dimmable		
DIMENSIONS	9.6"L x 7.5"W		
BULB NOT INCLUDED			
LAMP	1 x MR16/GU5.3 (bipin)/50W/12V Haloger		
	1 x MR16/GU5.3 (bipin)/12V LED		
Technical Information			
CEILING TYPE	Drywall with Trim		
HOUSING TYPE	New Construction NON IC		
HOUSING HEIGHT	4		
PRODUCT DIMENSIONS	Cutout: 3.69 inch		



COMPANY	PROJECT	FIXTURE TYPE	APPROVED BY	DATE

LTL19222

SPEC #