



BRANDWAC Lighting

DESCRIPTION

Precision Multiples 85CRI or 90CRI 010V NIC Housing features a frame and hanger bars made of 20 gauge galvanized steel with die-cast aluminum heat sink. Non-IC indicates that insulation must be kept a minimum of 3 inches away from housing. Includes 16.5 watts LED module with choice of 2700K, 3000K, 3500K, or 4000K color temperature. 90CRI option only available with 2700K or 3000K. 50,000 hour average lamp life. 365 degree horizontal rotation and 180 degree vertical rotation. Lights are fully retractable from housing. Abrasion resistant powder coat paint finish in Black. Accommodates surface up to 1 inch thick. Includes seven knockouts and four Romex style wiring connectors for ease of installation. Rated for branch wiring. Driver: Universal 120-277V input, 16.5 watt output. Dimmable with a 0-10V dimmer. ETL listed. Energy Star 5 year product warranty. Housing dimension: 14.9 inch width x 7.1 inch depth x 6 inch height. Trim available as an Invisible (trimless) or with trim option. Required trim and dimmer control, sold separately.



TRIM COLOR	N/A
BODY FINISH	Black
WATTAGE	32W
DIMMER	0-10V
DIMENSIONS	19.6"W x 6"H x 7.1"D
INTEGRATED LED MODULE	
LAMP	2 x LED/16W/120V LED
Technical Information	
LUMINOUS FLUX	1840 lumens
LUMENS/WATT	115.00
LAMP COLOR	2700K
COLOR RENDERING	85 CRI
BEAM ANGLE	20°
CENTER BEAM CBCP	8980 candlepower
LAMP LIFE	50000 hours
HOUSING TYPE	New Construction NON IC
SPEC #	WAC196806

COMPANY	PROJECT	FIXTURE TYPE	APPROVED BY	DATE