

IL116G Inground Uplight with Rock Guard

HAD21644

ⓓ

BRAND


Hadco by Signify


DESCRIPTION

IL116G Inground Uplight housing is fabricated from a single piece of compression-molded fiberglass reinforced polyester composite, pressure tested to ensure water will not wick or leak through. Finish in Bronze. Trim ring and Rock Guard is a textured composite material. Clear, convex, tempered, sodalime glass for high impact resistance. 2200 pound live-load rated, standard walk-over lens. One 75 watt 12 volt GU5.3 MR16 halogen lamp is required, but not included. Covered MR16 lamp is recommended to protect inner capsule lamp. Prewired with 3 foot pigtail of 18-2 AWG wire. Includes low voltage quick connector LVC3 for easy hook up to the low voltage supply cable not included. 6.6 inch diameter x 8.4 inch height. ETL listed for wet locations. Required remote transformer and optional mounting and optical accessories sold separately.



SHADE COLOR	Clear	
BODY FINISH	Bronze	
WATTAGE	75W	
DIMMER	Dimmable	
DIMENSIONS	6.6"W x 8.4"H	
BULB NOT INCLUDED		
LAMP	1 x MR16/GU5.3 (bipin)/75W/12V Halogen	
	1 x MR16/GU5.3 (bipin)/12V LED	
SPEC #	HAD21644	





APPROVED BY

PROJECT

FIXTURE TYPE

DATE

COMPANY