

Lightology

lightology.com
866-954-4489
07-29-26

Project: _____

Company: _____

Location: _____ Fixture Type: _____

SPEC #: **BAR22924**

Approved On: _____ Approved By: _____

Linear T8 Slide by Side Remote Ballast

By Bartco Lighting Co.



Description

Slide by Side T8 17, 25 or 32 Watt features adjustable stagger in a double width low profile linear fluorescent architectural fixture designed for remote ballast installations. A simple screw mechanism locks the sliding side of the fixture in place at the desired lamp overlap. Pre-wired for instant start ballast operation. Corrosion-resistant 20 gauge steel fully assembled housing. High reflectance white powder-coat finish. Available options are rapid start wiring, damp location, custom finishes and tube guard. Remote ballast and enclosure sold separately. General light distribution. UL and cUL listed. Minimum / maximum length for 17W is 24 5/8 inches- 35 3/8 inches. Minimum / maximum length for 25W is 36 5/8 inches- 53 3/8 inches. Minimum / maximum length for 32W is 48 5/8 inches- 70 7/8 inches. 2 7/16 inches high x 2 3/4 inches deep. Two 120 volt T8 Bipin linear fluorescent lamps not included. General light distribution.



Specifications

COLOR	White
BODY FINISH	White
WATTAGE	64W
DIMMER	Not Dimmable
DIMENSIONS	71"L x 3"W x 3"H
BULB NOT INCLUDED	2 x T8/T8 Bipin (G13)/32W/120V Fluorescent

Notes: