

Lightology

lightology.com
866-954-4489
07-30-26

Project: _____

Company: _____

Location: _____ Fixture Type: _____

SPEC #: **CNT24429**

Approved On: _____ Approved By: _____

disco LVR16-TE 4 Inch Non-IC New Construction Housing

By ConTech



Description

50W Low Voltage Downlight Standard Housing. For use in any type of ceiling application. Lamp housing is removable through ceiling aperture for access to junction box. Sure-grip springs permit housing to be lowered and precisely adjust to ceiling thicknesses from 1/2 inch to 1 inch. In insulated ceilings, maintain a minimum 3 inch clearance around housing. 12V 50W MR16 50W max, GU5.3 base. Porcelain socket assembly with Molex connector. Magnetic Class H transformer with Molex disconnect in J-box is fully dimmable with magnetic low voltage dimmers. Transformer has internal thermal protection. 120V Transformer Ratings: Input: 120VAC, 60Hz, .54A, 65VA. Output: 12VAC, 60Hz, 4.2A, 50W. cULus listed. Suitable for damp locations.



Specifications

REFLECTOR/BAFFLE COLOR N/A
BODY FINISH Galvanized Steel
WATTAGE 50W
DIMMER Low Voltage Magnetic
DIMENSIONS 10.5"L x 5.75"W x 5.5"H
BULB NOT INCLUDED 1 x MR16/GU5.3 (bipin)/50W/12V Halogen
OTHER BULB OPTIONS 1 x MR16/GU5.3 (bipin)/12V LED

Technical Information

HOUSING HEIGHT 6"
HOUSING TYPE Remodel NON IC
CEILING TYPE Drywall with Trim

Notes: