

Lightology

lightology.com
866-954-4489
07-30-26

Project: _____
Company: _____
Location: _____ Fixture Type: _____
SPEC #: **CNT24443**
Approved On: _____ Approved By: _____

Symphony Low Voltage Mini Track

By ConTech



Description

Symphony Mini-Track System is perfect for residential and commercial spaces that require a very low profile lighting system. Solid 10 gauge copper conductors with Noryl insulators placed in heavy guage extruded aluminum channels for durability and system integrity. Symphony Mini-track will not degrade or warp like plastic track systems. The Mini-track system offers true versatility with a variety of power feed, connection and support accessories. Finish available in black, white, silver and unfinished aluminum. Available in 2, 4, 6 and 8 feet lengths. The 2, 4 and 6 foot sections are pre-drilled with two mounting holes and and the 8 foot section has three mounting holes. Track sections may be cut in the field, but take care to back out the bus bar before cutting. Every track section is supplied with an MLA-1 End Feed Connector/Cover and an MLA-11 End Cap. Polarity is not an issue with low voltage lighting. Maximum power ratings are 300 watts at 12 volts or 600 watts at 24 volts for higher power requirements. c/UL listed. Suitable for dry locations. 0.81W x 0.44H x 96L.

Specifications

COLOR	N/A
BODY FINISH	Black
WATTAGE	N/A
DIMMER	N/A
DIMENSIONS	96"L x 0.81"W x 0.44"H
BULB	N/A



Notes: