

## RL38 6 Inch New Construction Non IC Housing











BRAND ConTech

## DESCRIPTION

RL38 6 Inch Universal New Construction Non-IC Housing features a White steel housing with dual extension bars adjustable for 16 and 24 inch center joists. Adjustable socket mounting plate (vertical position). Non-IC designation requires that insulation be kept a minimum of 3 inches away from housing. One 120 volt, A-type, PAR30, BR30, BR40, PAR38 or R40 heat lamp with medium base or LED equivalent is required, but not included. Lamp type and wattage dependent upon housing/ trim combination (see attached manufacturer specification). Halogen and incandescent dimmable with a standard incandescent dimmer. Consult bulb manufacturer for dimmer compatibility when using LED bulb option. Input voltage 120V AC, 60Hz. cCSAus Certified. Suitable for damp locations. 7.5 inch width x 11 inch length x 6.75 inch height. A complete fixture includes a housing and trim, sold separately.

TRIM COLOR N/A BODY FINISH Galvanized Steel WATTAGE 150\\/ DIMMER Dimmable DIMENSIONS 11"L x 7.5"W x 6.75"H **BULB NOT INCLUDED** LAMP

1 x PAR38/Medium (E26)/150W/120V Halogen

1 x PAR38/Medium (F26)/120V LFD

1 x A19/Medium (E26)/120V Incandescent 1 x A19/Medium (E26)/120V LED


1 x A19/Medium (E26)/12V Halogen

Technical Information

CEILING TYPE Drywall with Trim HOUSING TYPE New Construction NON IC HOUSING HEIGHT APERTURE SHAPE Round

SPEC # CNT24454





COMPANY PROJECT FIXTURE TYPE APPROVED BY DATE

Ceiling Opening: 6-1/2\*

Ceiling Thickness: 1/2" - 1-1/2"