

Lightology

lightology.com
866-954-4489
07-30-26

Project: _____
Company: _____
Location: _____ Fixture Type: _____
SPEC #: **GHI24933**
Approved On: _____ Approved By: _____

Microneo SS Ring 38 Degree In-Ground Recessed

By Ghidini Illuminazione



Description

Microneo stainless steel ring trim compact sized drive over in-ground recessed light with a 10-38 degree beam spread features a clear sodium calcium tempered glass 6/8mm thick diffuser and AISI 316L 2mm thick stainless steel trim. Supports a maximum static load pressure of 5, 400 lbs. Rough in housing made of aluminum included. Suitable for use in poured concrete. 12 inch drainage area required. 20 watt 12 volt MR11 halogen lamp not included. Remote transformer not included. EN-AB47100 die-cast aluminum body is highly resistant to oxidation. Silicone sealing gasket. A2 stainless steel screws dipped in water resistant lubricating solution facilitates easy opening for maintenance. Accessories include: colored filters. IP67 rated. ETL listed for wet location. Made in Italy.



Specifications

COLOR Clear
BODY FINISH Stainless Steel
WATTAGE 20W
DIMMER Dimmable
DIMENSIONS 3.94"L x 3.94"W x 4.5"H
BULB NOT INCLUDED 1 x MR11/Bipin/20W/12V Halogen
COUNTRY OF ORIGIN Italy

Notes: