

Lightology

lightology.com
866-954-4489
07-30-26

Project: _____

Company: _____

Location: _____ Fixture Type: _____

SPEC #: **GHI25001**

Approved On: _____ Approved By: _____

Margin Flush Aluminum Trim 54 Degree Beam Recessed Wall Fi

By Ghidini Illuminazione



Description

Margin wall flush aluminum trim exterior wall recessed fixture with 54 degree beam spread features a clear or frost sodium calcium tempered glass 4mm thick diffuser and a light grey or black UV resistant polyester powder coat finish, which is highly resistant to corrosion. Non flush aluminum or stainless steel trim versions available. Rough in housing made of Cataphoreses treated iron included. Suitable for use in poured concrete. 13 watt 120 volt G24q-1 base compact fluorescent lamp not included. Electronic ballast included. Also available in blue or white ED, incandescent and halogen versions. EN-AB47100 die-cast aluminum body is highly resistant to oxidation. Silicone sealing gasket. A2 stainless steel screws dipped in water resistant lubricating solution facilitates easy opening for maintenance. IP66 rated. ETL listed for wet location. Made in Italy. 9.6"W x 2.7"H. Housing depth 5.28".

Specifications

COLOR	Frosted
BODY FINISH	Black
WATTAGE	13W
DIMMER	Not Dimmable
DIMENSIONS	5.28"L x 9.57"W x 2.73"H
BULB NOT INCLUDED	1 x T4/G24q-1/13W/120V Compact Fluorescent
COUNTRY OF ORIGIN	Italy

Technical Information

BEAM ANGLE	54°
------------	-----



Notes:

--