



BRAND

Juno Lighting

DESCRIPTION

CV6 6 inch CFL 26/32W TC housing requires 3 inch spacing from insulation. Commercial butterfly mounting brackets. Use with optional HB-1 residential bar hanger conversion kit for joist construction. One 26W or 32W triple tube compact fluorescent lamp CFTR26W/GX24Q-3 or CFTR32W/GX24Q-3. 4 pin electronic. Vented, extruded aluminum housing with heat dissipating fins. Single-position, keyed reflector attachment. 120V thru 277V HPF electronic with end-of-life lamp protection. 347V HPF electronic available in Canada. Optional dimming ballast available. UL listed/CSA certified. UL listed for through-branch wiring and damp locations. Product mechanically protected against improper use of lamps. Union made AFL-CIO. UL and CSA listed for feed through and damp location. 7 5/8 in W x 9 3/8 in H



TRIM COLOR	N/A
BODY FINISH	Aluminum
WATTAGE	32W
DIMMER	Not Dimmable
DIMENSIONS	11.5"L x 7.625"W x 9.375"H
BULB NOT INCLUDED	
LAMP	1 x T4/GX24q-3/32W/120V Compact Fluorescent

Technical Information

CEILING TYPE	Drywall with Trim
HOUSING TYPE	Remodel NON IC
HOUSING HEIGHT	10"

SPEC # JUN25844

COMPANY	PROJECT	FIXTURE TYPE	APPROVED BY	DATE