

Lightology

lightology.com
866-954-4489
07-29-26

Project: _____
Company: _____
Location: _____ Fixture Type: _____
SPEC #: **JUN26382**
Approved On: _____ Approved By: _____

TC20 5 Inch New Construction Non-IC Housing By Juno Lighting



Description

TC20 5 Inch Universal Non-IC New Construction Housing is designed for use in non-insulated areas. If installed where insulation is present, the insulation must be pulled back 3 inches from all sides of the housing. Accommodates ceiling thickness up to 1 inch. Lamp type and wattage dependent upon housing/trim combination (see attached Juno manufacturer specification). Incandescent/halogen dimmable with a standard incandescent dimmer. Consult lamp manufacturer for dimmer compatibility when using an LED equivalent lamp. UL listed for through-branch wiring, damp locations and IP. Trims 210N, 211 and 212N are wet location approved for covered ceiling applications. Trims 215 and 216 are wet location approved for covered ceiling applications when used with outdoor rated lamps. 11.9 inch length x 6.75 inch width x 7.5 inch height. A complete fixture includes a housing and trim, sold separately.

Specifications


REFLECTOR/BAFFLE COLOR	N/A
BODY FINISH	Aluminum
WATTAGE	N/A
DIMMER	Dimmable
DIMENSIONS	11.9"L x 6.75"W x 7.5"H
BULB NOT INCLUDED	1 x BR30/Medium (E26)/120V Incandescent
OTHER BULB OPTIONS	1 x A19/Medium (E26)/120V LED 1 x PAR20/Medium (E26)/120V Halogen 1 x PAR20/Medium (E26)/120V LED 1 x PAR30L/Medium (E26)/120V Halogen 1 x PAR30L/Medium (E26)/120V LED 1 x PAR30S/Medium (E26)/120V Halogen 1 x PAR30S/Medium (E26)/120V LED 1 x R20/Medium (E26)/120V Incandescent 1 x R20/Medium (E26)/120V LED A19/Medium (E26)/120V Incandescent BR30/Medium (E26)/120V LED

Technical Information

PRODUCT DIMENSIONS	Ceiling Cutout: 5.63 in
HOUSING HEIGHT	8"
HOUSING TYPE	New Construction NON IC
CEILING TYPE	Drywall with Trim



Shown in aluminum



CLICK TO VIEW PRODUCT

Notes: