

Lightology

lightology.com
866-954-4489
07-29-26

Project: _____

Company: _____

Location: _____ Fixture Type: _____

SPEC #: **CLT3792**

Approved On: _____ Approved By: _____

Low Voltage 3.5IN New Construction Electronic IC Housing

By Contrast Lighting



Description


ISMR3000E35 3.5 Inch Low Voltage IC Airtight New Construction Housing is designed for insulated new construction applications. IC designation allows housing to be in direct contact with insulation. Below ceiling accessible. Takes up to a 7/8 inch ceiling thickness. Low voltage 12 volt electronic transformer included. One 35 watt, 12 volt GU5.3 MR16 bulb is required, but not included. Dimmable with a low voltage electronic dimmer. See attached manufacturer dimmer compatibility reference when using LED bulb option. Suitable for damp locations. UL listed. 3.75 inch ceiling cut out. 15.25 inch length x 8.25 inch width x 7.9 inch height. A complete fixture includes a housing and trim, sold separately.

Specifications

REFLECTOR/BAFFLE COLOR N/A
BODY FINISH Galvanized Steel
WATTAGE 35W
DIMMER Low Voltage Electronic
DIMENSIONS 15.25"L x 8.25"W x 7.9"H
BULB NOT INCLUDED 1 x MR16/GU5.3 (bipin)/35W/12V Halogen
OTHER BULB OPTIONS MR16/GU5.3 (bipin)/12V LED

Technical Information

PRODUCT DIMENSIONS Cutout 3 3/4"
APERTURE SIZE 3.500"
HOUSING HEIGHT 8"
HOUSING TYPE New construction IC Airtight
CEILING TYPE Drywall with Trim



Notes: