



lightology.com
866-954-4489
07-29-26

Project: _____	
Company: _____	
Location: _____	Fixture Type: _____
SPEC #: CLT3799	
Approved On: _____	Approved By: _____

Low Voltage 4IN Shallow Remodel Electronic Non-IC Housing

By Contrast Lighting



Description


IT2000CE 4 Inch Low Voltage Non-IC Shallow Remodel Housing is designed for non insulated remodel applications. Non-IC designation requires that insulation be kept a minimum of 3 inches away from housing. Below ceiling accessible. Takes from 1/2 to 1.25 inch ceiling thickness. Low voltage 12 volt electronic transformer included. One 42 watt, 12 volt GU5.3 MR16 bulb is required, but not included. Dimmable with a low voltage electronic dimmer. See attached manufacturer dimmer compatibility reference when using LED bulb option. Suitable for damp locations. UL listed. 3 5/8 inch ceiling cut out. 13.6 inch length x 5 inch width x 3.75 inch height. A complete fixture includes a housing and trim, sold separately.

Specifications

REFLECTOR/BAFFLE COLOR	N/A
BODY FINISH	Galvanized Steel
WATTAGE	42W
DIMMER	Low Voltage Electronic
DIMENSIONS	13.6"L x 5"W x 3.75"H
BULB NOT INCLUDED	MR16/GU5.3 (bipin)/42W/12V Halogen
OTHER BULB OPTIONS	MR16/GU5.3 (bipin)/12V LED

Technical Information

PRODUCT DIMENSIONS	Cutout: 4 1/4"
APERTURE SIZE	4.000"
HOUSING HEIGHT	4"
HOUSING TYPE	Remodel NON IC
CEILING TYPE	Drywall with Trim



Notes: