



lightology.com
866-954-4489
07-29-26

Project: _____	
Company: _____	
Location: _____	Fixture Type: _____
SPEC #: CLT3801	
Approved On: _____	Approved By: _____

Low Voltage 3.5IN Shallow Remodel Electronic Non-IC Housing

By Contrast Lighting



Description



IT3000CE 3.5 Inch Low Voltage Non-IC Shallow Remodel Housing is designed for non insulated remodel applications. Non-IC designation requires that insulation be kept a minimum of 3 inches away from housing. Below ceiling accessible. Takes up to a 7/8 inch ceiling thickness. Low voltage 12 volt electronic transformer included. One 35-37 watt, 12 volt GU5.3 MR16 bulb is required, but not included. Wattage dependent on housing/trim combination. Dimmable with a low voltage electronic dimmer. See attached manufacturer dimmer compatibility reference when using LED bulb option. Suitable for damp locations. UL listed. 3 5/8 inch ceiling cut out. 11.6 inch length x 4.7 inch width x 3.7 inch height. A complete fixture includes a housing and trim, sold separately.

Specifications

REFLECTOR/BAFFLE COLOR	N/A
BODY FINISH	Galvanized Steel
WATTAGE	37W
DIMMER	Low Voltage Electronic
DIMENSIONS	11.6"L x 4.7"W x 3.7"H
BULB NOT INCLUDED	MR16/GU5.3 (bipin)/37W/12V Halogen
OTHER BULB OPTIONS	1 x MR16/GU5.3 (bipin)/12V LED

Technical Information

PRODUCT DIMENSIONS	Cutout: 3 5/8"
APERTURE SIZE	3.500"
HOUSING HEIGHT	4"
HOUSING TYPE	Remodel NON IC
CEILING TYPE	Drywall with Trim



Notes: