

Lightology

lightology.com
866-954-4489
07-30-26

Project: _____

Company: _____

Location: _____ Fixture Type: _____

SPEC #: **CLT3802**

Approved On: _____ Approved By: _____

Low Voltage 3.5IN Shallow Remodel Magnetic Non-IC Housing

By Contrast Lighting



Description



IT3000CM 3.5 Inch Low Voltage Non-IC Shallow Remodel Housing is designed for non insulated remodel applications. Non-IC designation requires that insulation be kept a minimum of 3 inches away from housing. Below ceiling accessible. Takes up to a 7/8 inch ceiling thickness. Low voltage 12 volt magnetic transformer included. One 35 watt, 12 volt GU5.3 MR16 bulb is required, but not included. Dimmable with a low voltage magnetic dimmer. Consult with bulb manufacturer for low voltage magnetic dimmer compatibility when using LED bulb option. Suitable for damp locations. UL listed. 3 5/8 inch ceiling cut out. 13 inch length x 4.7 inch width x 3.7 inch height. A complete fixture includes a housing and trim, sold separately.

Specifications

REFLECTOR/BAFFLE COLOR	N/A
BODY FINISH	Galvanized Steel
WATTAGE	35W
DIMMER	Low Voltage Magnetic
DIMENSIONS	13"L x 4.7"W x 3.7"H
BULB NOT INCLUDED	MR16/GU5.3 (bipin)/35W/12V Halogen
OTHER BULB OPTIONS	MR16/GU5.3 (bipin)/12V LED

Technical Information

PRODUCT DIMENSIONS	Cutout: 3 5/8 inch
APERTURE SIZE	3.500"
HOUSING HEIGHT	4"
HOUSING TYPE	Remodel NON IC
CEILING TYPE	Drywall with Trim



Notes: