

IT3000LE 3.5 Inch 42-50W ELV Non-IC Remodel Housing



Description:

IT3000LE 3.5 Inch Low Voltage Non-IC Remodel Housing is designed for non insulated remodel applications. Non-IC designation requires that insulation be kept a minimum of 3 inches away from housing. Below ceiling accessible. Takes up to 7/8 inch ceiling thickness. Low voltage 12 volt electronic transformer is included. One 42-50 watt, 12 volt GU5.3 MR16 bulb is required, but not included. Dimmable with a low voltage electronic dimmer. See attached manufacturer dimmer compatibility reference when using LED bulb option. 3 5/8 inch ceiling cut out. 13.4 inch length x 4.5 inch width x 7.1 inch height. A complete fixture includes a housing and trim, sold separately.

Shown in: Galvanized Steel

List Price: \$104.00
 Our Price: \$74.88

Shade Color: N/A
 Body Finish: Galvanized Steel
 Lamp: 1 x MR16/GU5.3 (bipin)/50W/12V Halogen
 1 x MR16/GU5.3 (bipin)/12V LED
 Wattage: 50W
 Dimmer: Low Voltage Electronic
 Dimensions: 13.4"L x 7.1"H x 4.5"W

Technical Information

Ceiling Type: Drywall with Trim
 Housing Type: Remodel NON IC
 Housing Height: 7"
 Aperture Size: 3.500"
 Product Dimensions: Cutout 3 5/8"

Product Number: CLT3804			
Company:		Fixture Type:	Date: Feb 25, 2018
Project:		Approved By:	

#0314RE-IT3000L-004H1-OOMT

Phone: 866-954-4489 Fax: (773) 883-6131

Address: 1718 W. Fullerton Ave. Chicago IL 60614

www.Lightology.com