

# Lightology

lightology.com  
866-954-4489  
05-25-26

Project: \_\_\_\_\_  
 Company: \_\_\_\_\_  
 Location: \_\_\_\_\_ Fixture Type: \_\_\_\_\_  
 SPEC #: **HAD400558**  
 Approved On: \_\_\_\_\_ Approved By: \_\_\_\_\_

## IUL516 LED Composite Inground Uplight

By Hadco by Signify



### Description

IUL516 LED Composite Inground Uplight is fabricated from one piece injection molded high performance polymer composite. Composite is textured, pressure formed, molded in color in Bronze. Lens ring is a single piece injection molded high performance polymer with gasketed lens and twist off operation for ease of maintenance. Clear convex, tempered glass furnished with silicone O-ring for watertight seal. Includes one 7 watt 12 volt GU5.3 MR16 LED lamp with 25 degree beam spread, 3000K color temperature, 460 lumens. 25,000 hour average lamp life. Pre-wired with 3 foot pigtail of 18-2 AWG wire. Includes low voltage quick connector LVC3 for easy hook up to the low voltage supply cable, sold separately. 4.1 inch diameter x 4.4 inch height. ETL listed for wet locations. 5 year limited warranty. Requires remote transformer, sold separately.

### Specifications


COLOR	N/A
BODY FINISH	Bronze
WATTAGE	7W
DIMMER	Dimmable
DIMENSIONS	4.1"W x 4.4"H
BULB INCLUDED	1 x MR16/GU5.3 (bipin)/7W/12V LED

### Technical Information

LAMP LIFE	25000 hours
BEAM ANGLE	25°
LAMP COLOR	3000K
LUMENS/WATT	65.71
LUMINOUS FLUX	460 lumens



Shown in bronze



CLICK TO VIEW PRODUCT

Notes: