

Lightology

lightology.com
866-954-4489
07-29-26

Project: _____

Company: _____

Location: _____ Fixture Type: _____

SPEC #: **HAL40737**

Approved On: _____ Approved By: _____

H1499ICAT 4 Inch IC Air-Tite New Construction Housing

By Halo



Description

H1499ICAT 4 inch IC Air-Tite new construction housing features a double wall aluminum construction for greater heat dissipation, gasketed to prevent airflow from heated or air conditioned spaces, and is designed for use in insulated ceilings with direct contact to insulation. May be used to meet insulated ceiling and restricted air-flow requirements. The inner housing can be removed from the plaster frame to provide access to the junction box. Includes a magnetic transformer. UL listed. Damp location listed. Wet location listed with select trim options. Lamp ratings based on trim selected, sold separately.



Specifications

REFLECTOR/BAFFLE COLOR	N/A
BODY FINISH	Aluminum
WATTAGE	N/A
DIMMER	Low Voltage Magnetic
DIMENSIONS	9.5"L x 12.5"W x 7.38"H
BULB NOT INCLUDED	1 x MR16/GU5.3 (bipin)/12V Halogen
OTHER BULB OPTIONS	1 x MR16/GU5.3 (bipin)/12V LED

Technical Information

PRODUCT DIMENSIONS	Ceiling Cutout: 4.5 In
APERTURE SHAPE	Round
HOUSING HEIGHT	8"
HOUSING TYPE	New construction IC Airtight
CEILING TYPE	Drywall with Trim

Notes: