

BRAND

PureEdge Lighting


DESCRIPTION

Soft Line mounting hardware for indirect lighting uses white or RGB LED Soft Strip (sold separately) to provide soft, ambient, indirect illumination for decorative and architectural applications. For compact shipment and storage, Soft Line coils like a retractable tape measure. When uncoiled, the Soft Line becomes a 1 inch wide cupped aluminum channel that can be mounted on any angle between opposing wall, ceiling or floor surfaces. Available in 20 and 40 feet lengths. Soft Line is field-cuttable, making it easy to configure custom lengths up to 40 feet. The suspended line, 1 to 2 feet away from the surface, indirectly illuminates with the use of the any LED Soft Strip (sold separately). This cupped form contributes to the luminaire's structural rigidity, acts as a heat sink, and also shields the LED light source and related wiring from view. For indirect, warm white LED use SS2P-WW 12V or 24V. For indirect, color changing LED use SS3-RGB-24V. Requires soft line turnbuckles, Soft Strip and power supply, sold separately. See Soft Strip specification for required power supply.



SHADE COLOR	N/A
BODY FINISH	Satin Aluminum
WATTAGE	N/A
DIMMER	N/A
DIMENSIONS	240"L x 1"W
LAMP	N/A

SPEC # EDG56285



COMPANY

PROJECT

FIXTURE TYPE

APPROVED BY

DATE