



BRAND

PureEdge Lighting

DESCRIPTION

Light Channel Micro Wall Grazer LED features 12 volt Soft Strip Premium (SS2P) inside a slim aluminum extrusion. The asymmetrical 10 degree lens is ideal for creating dramatic grazing effects. The flexible linear system is sold in 2 inch increments up to 96 inches and includes a mounting clip with each 2 foot section. Fixtures can be linked end-to-end with plug in or flexible connectors for a maximum length of 25 feet. Includes 6 foot power feed cable. At only 2.3 watts, each foot of channel contains 36 Warm White 3000K, 80CRI LEDs, delivering 115 lumens. Average lamp life 32,000 hours. Requires a 12 volt 60 watt PSB-60W-ELV-12VDC power supply, dimmable with a low voltage electronic dimmer (recommended Lutron Diva DVELV-300P, Lutron Skylark SELV-300P, or Lutron Maestro MAELV-600), sold separately. ETL listed. Fixture includes a 5 year warranty. Major components made and assembled in the USA. Limited Quantities Available. Please call for more information. Product is built to order.



SHADE COLOR	N/A
BODY FINISH	Satin Aluminum
WATTAGE	8.8W
DIMMER	Dimmable
DIMENSIONS	46"L x 0.8"W x 0.79"H
INTEGRATED LED MODULE	
LAMP	1 x LED/8.81W/12V LED

Technical Information

LUMINOUS FLUX	441 lumens
LUMENS/WATT	50.06
LAMP COLOR	3000K
COLOR RENDERING	80 CRI

SPEC # EDG56917



COMPANY	PROJECT	FIXTURE TYPE	APPROVED BY	DATE