

Lightology

lightology.com
866-954-4489
07-29-26

Project: _____
Company: _____
Location: _____ Fixture Type: _____
SPEC #: **EDG57192**
Approved On: _____ Approved By: _____

Light Channel Surface 2.3W 12V

By PureEdge Lighting



Description

The Light Channel Surface Mount LED features 12 volt Soft Strip Premium SS2P inside a slim aluminum extrusion. The 61 degree white diffuser (DWW) lens projects a clean line of light and eliminates LED dots. Available in a 12 or 60 inch length in Satin Aluminum and includes LC-MCL standard mounting clips with every 2 feet of Light Channel. Fixtures can be linked end to end with plug in or flexible connectors for a maximum of 25 feet before refeeding the power. Includes a 6 foot power feed cable. 2.3 watts per foot delivering 115 lumens. 3000K color temperature, 80CRI. 32,000 hour average lamp life. Powered by a 60 watt 12 volt power supply, dimmable with an electronic low voltage dimmer, sold separately. Recommended dimmers include Lutron Diva DVELV-300P or Lutron Skylark SELV-300P, or Lutron Maestro MAELV-600, sold separately. ETL listed. Fixture includes a 5 year warranty. Major components assembled in the USA. Limited Quantities Available. Please call for more information.

Specifications

COLOR Diffused Lens
BODY FINISH Satin Aluminum
WATTAGE 16.1W
DIMMER Low Voltage Electronic
DIMENSIONS 84"L x 0.8"W x 0.68"H
INTEGRATED LED MODULE 1 x LED/16.1W/12V LED

Technical Information

LAMP LIFE 32000 hours
COLOR RENDERING 80 CRI
LAMP COLOR 3000K
LUMENS/WATT 50.00
LUMINOUS FLUX 805 lumens



Notes: