



BRAND

PureEdge Lighting

DESCRIPTION

The Light Channel Surface Mount LED features 12 volt Soft Strip Premium SS2P inside a slim aluminum extrusion. The 61 degree white diffuser (DWW) lens projects a clean line of light and eliminates LED dots. Available in a 12 or 60 inch length in Satin Aluminum and includes LC-MCL standard mounting clips with every 2 feet of Light Channel. Fixtures can be linked end to end with plug in or flexible connectors for a maximum of 25 feet before refeeding the power. Includes a 6 foot power feed cable. 2.3 watts per foot delivering 115 lumens. 3000K color temperature, 80CRI. 32,000 hour average lamp life. Powered by a 60 watt 12 volt power supply, dimmable with an electronic low voltage dimmer, sold separately. Recommended dimmers include Lutron Diva DVELV-300P or Lutron Skylark SELV-300P, or Lutron Maestro MAELV-600, sold separately. ETL listed. Fixture includes a 5 year warranty. Major components assembled in the USA. Limited Quantities Available. Please call for more information.



SHADE COLOR	Diffused Lens
BODY FINISH	Satin Aluminum
WATTAGE	18.4W
DIMMER	Low Voltage Electronic
DIMENSIONS	96"L x 0.8"W x 0.68"H
INTEGRATED LED MODULE	
LAMP	1 x LED/18.4W/12V LED

Technical Information

LUMINOUS FLUX	920 lumens
LUMENS/WATT	50.00
LAMP COLOR	3000K
COLOR RENDERING	80 CRI

SPEC #	EDG57227
--------	----------



COMPANY

PROJECT

FIXTURE TYPE

APPROVED BY

DATE