

Lightology

lightology.com
866-954-4489
07-30-26

Project: _____
Company: _____
Location: _____ Fixture Type: _____
SPEC #: **LTL59220**
Approved On: _____ Approved By: _____

Skyway LED 2 X 2 Recessed Troffer

By Lightolier by Signify



Description


Skyway LED 2 X 2 Static Recessed Grid Troffer features a Pattern 19 0.156 inch virgin acrylic center lens with frost white acrylic side lenses. Alternating lens textures creates visual interest while shielding the LEDs from direct view and preventing pixilation. Delivers 2500 lumens with 30.4 watts, 4000K color temperature. High efficiency LEDs have 50,000 hour average rated life at 70 percent lumen maintenance. 120-277 Universal voltage. Field replaceable LED array and drivers accessible from below. Factory calibrated intelligent driver capable of providing various lumen outputs to balance energy savings with lighting application needs. Dimmable LED driver included (consult factory for dimming options). Integrated thermal management system conducts heat away from LEDs and transfers it to the surrounding environment. Black body to dissipate heat from LEDs. Not for continuous row mounting. Includes earthquake/hold down clips. UL listed. 5 year product warranty. Dimensions: 24 inch width x 24 inch depth x 5 inch height.

Specifications

COLOR Frosted
BODY FINISH Galvanized Steel
WATTAGE 30.4W
DIMMER N/A
DIMENSIONS 24"L x 24"W x 5"H
INTEGRATED LED MODULE LED/30.4W/120V LED

Technical Information

LAMP COLOR 4000K
LUMENS/WATT 78.32
LUMINOUS FLUX 2381 lumens



Notes: