

Lightology

lightology.com
866-954-4489
07-30-26

Project: _____
Company: _____
Location: _____ Fixture Type: _____
SPEC #: **LUT60308**
Approved On: _____ Approved By: _____

PP-20 Dimmer Power Pack

By Lutron



Description

PP-20 Dimmer Power Pack is for use with Lutron NTSTV (over 8 amps) and DVTV dimmers, microOS ceiling mount occupancy sensors and 0-10V dimming ballasts. Features include teflon insulated pigtails and ABS housing fire-rated for mounting in ceiling plenums. Simple junction box mounting in a standard knockout with all needed hardware included. Dual voltage 120/277V compatibility. Max load 20 amps (16 continuous). Operates up to five Lutron microOS ceiling mounted occupancy sensors. Up to 10 power packs can be connected to one Lutron 0-10VDC ballast control for switching of multiple circuits. For use in single pole applications only-not compatible with 3-way switches. Total length of low voltage wiring between the power pack and ceiling mounted occupancy sensor or 0-10VDC ballast control should be less than 500 feet. UL listed. 3 inch width x 2.5 inch height x 1.75 inch depth.

Specifications

COLOR	N/A
BODY FINISH	Black
WATTAGE	N/A
DIMMER	N/A
DIMENSIONS	3"W x 2.5"H x 1.75"D
BULB	N/A



Notes: