

Lightology

lightology.com
866-954-4489
07-29-26

Project: _____

Company: _____

Location: _____ Fixture Type: _____

SPEC #: **EDG69724**

Approved On: _____ Approved By: _____

Soft Line LED 24V RGB Single Row Indirect By PureEdge Lighting



Description

Soft Line LED System for Indirect Lighting uses RGB to provide soft, ambient, indirect illumination for decorative and architectural applications. For compact shipment and storage, Soft Line coils like a retractable tape measure. When uncoiled, the Soft Line becomes a 1.25 inch wide cupped, rigid aluminum channel that can be mounted on any angle between opposing wall, ceiling or floor surfaces. Soft Line is field-cuttable. Max length 16 feet before re-feeding at both ends. SL-RGB features a single row of 24 volt Soft Strip in Red, Green & Blue colors. SL-RGB kit includes Soft Line channel, a pair of power feed and non-power feed turnbuckles and a single row of RGB LED Soft Strip. Soft Line 24 inch standoff, sold separately. Turnbuckles support Soft Line on any angle from 0-60 degrees, feed power from one end and mount to a standard 4 inch square electrical box with round plaster ring. Turnbuckles may be reversed and mounted (opposite the power feed) to a ceiling, wall or floor. System is powered by a remote RGB Power Supply with DMX Driver. CDMX1-RGBW, CDP and CTP Controller options send commands to RGB drivers for color changing Soft Strip. Power supply, standoff, and controller sold separately.

Specifications

COLOR	N/A
BODY FINISH	Satin Aluminum
WATTAGE	26W
DIMMER	Dimmable
DIMENSIONS	120"L x 1.25"W x 1.5"H
INTEGRATED LED MODULE	10 x LED/2.6W/24V LED

Technical Information

LAMP LIFE	50000 hours
-----------	-------------



Notes: