

Lightology

lightology.com
866-954-4489
07-29-26

Project: _____
Company: _____
Location: _____ Fixture Type: _____
SPEC #: **LTL82473**
Approved On: _____ Approved By: _____

Calculite 4.5 Inch Square 0-10 LED New Construction Housing

By Lightolier by Signify



Description


Calculite 4.5 Inch Square 0-10 Dim New Construction 20 Watt 120 Volt LED Housing. Accommodates mounting to virtually any ceiling system using pre-installed mounting bars. Alignment holes and markings allow fixture to be preset prior to installation. Rotating plate allows for 360 degree adjustment during installation prior to connection of power supply to trim. Telescoping locking bars extend to 30 inches and lock securely into position. Includes 0-10 LED power supply dimmable with a 0-10 dimmer. Input Voltage: 120V. Input Power: 20 Watts. Input Frequency: 50/60Hz. LED Driver: 350mA. Input Current: 0.167. 50,000 hour average lamp life at 70 percent lumen maintenance. Overload and short circuit protected. UL listed. Suitable for wet locations. Dimensions: 20 inch length x 10.75 inch width x 5.75 inch height. 5 3/8 inch square cut out. A complete fixture consists of a housing, light engine and trim kit.

Specifications

REFLECTOR/BAFFLE COLOR N/A
BODY FINISH Galvanized Steel
WATTAGE 20W
DIMMER 0-10V
DIMENSIONS 20"L x 10.75"W x 5.75"H
BULB NOT INCLUDED LED/20W/120V LED

Technical Information

APERTURE SHAPE Square
HOUSING HEIGHT 6"
HOUSING TYPE New Construction NON IC
CEILING TYPE Drywall with Trim



Notes: