

Cirrus Ceiling S1 Lens Downlight w/ Remote Power

SPEC # EDG90370



DESIGNERGregory KayBRANDPureEdge Lighting

DESCRIPTION


Cirrus Ceiling Channel S1 Lens Downlight with Remote Power is a linear LED fixture that offers direct light in a clean, contemporary style. Cirrus is available in various increments from 12 to 480 inches, features a square lens with 105 degree beam, three wattage options, and a spectrum of color temperature options. Maximum shipping length for Chrome is 84 inches. Includes a 4.6 inch square canopy. May be ordered with a Slim Profile Channel Junction Box (C-IRE-JBOX), sold separately. Mounting clips (CC-MCL) are included for use every 18 inches. Canopy mounts to a standard junction box either using the PS-60L-ELV-24VDC (50 Watt 24 Volt DC Power Supply) which fits inside junction box, or from a 24VDC remote Universal (UNI) power supply. Universal dimming with UNI power supply (TRIAC/ ELV/0-10V). ELV dimming with PS-60L-ELV power supply. Required power supply, dimmer control, and optional accessories sold separately. Note: Limited quantities available in Bronze finish.

| NTEGRATED LED MODULE | N/A Satin Aluminum 2W Dimmable 12"L x 0.9"W x 0.9"H |
|--|--|
| BODY FINISH VATTAGE DIMMER DIMENSIONS NTEGRATED LED MODULE AMP | Satin Aluminum 2W Dimmable 12"L x 0.9"W x 0.9"H |
| VATTAGE DIMMER DIMENSIONS NTEGRATED LED MODULE AMP | 2W Dimmable 12"L x 0.9"W x 0.9"H |
| DIMMER DIMENSIONS NTEGRATED LED MODULE AMP | Dimmable 12"L x 0.9"W x 0.9"H |
| DIMENSIONS NTEGRATED LED MODULE AMP | 12"L x 0.9"W x 0.9"H |
| NTEGRATED LED MODULE AMP Technical Information | |
| AMP 1 | 1 x LED/2W/24V LED |
| echnical Information | 1 x LED/2W/24V LED |
| | |
| | |
| AMP COLOR | |
| | 2700K |
| OLOR RENDERING | 95 CRI |
| BEAM ANGLE | 105° |
| AMP LIFE | 50000 hours |



Shown in: Satin Aluminum





| COMPANY | PROJECT | FIXTURE TYPE | APPROVED BY | DATE |
|---------|---------|--------------|-------------|------|
| | | | | |

EDG90370

SPEC #