Lightology

lightology.com
866-954-4489
07-29-26

Project:

Company:

Location: Fixture Type:

SPEC #: **EDG99491**

Approved On: Approved By:

Cirrus D1 Linear Suspension w/Power/Center Feed

By PureEdge Lighting

Description

The Cirrus Power D1 Lens Linear Downlight Suspension with Center Feed is a linear LED fixture that offers direct light in a clean, contemporary style. Cirrus is available in various increments from 36 to 120 inches with a 100 degree white diffused or 60 degree clear frosted direct downlight lens, optional black or white louver, a variety of finishes, three wattage options, and a spectrum of color temperature options. Includes a linear canopy (12 inch for lengths 36-96 inch / 26 inch for lengths 99-120 inch) and 12 foot adjustable coaxial cables. Additional aircraft cables provided for support when fixture exceeds 72 inches. Note: Product is built to order. Includes a 120V/24VDC Universal (UNI) LED power supply, dimmable with an electronic low voltage (ELV), Triac (magnetic) or 0-10V dimmer, sold separately.

Shown in satin nickel / white lens





Specifications

COLOR	White Lens
BODY FINISH	Satin Nickel
WATTAGE	21W
DIMMER	Low Voltage Electronic
DIMENSIONS	36"L x 0.9"W x 0.9"H
INTEGRATED LED MODULE	3 x LED/7W/24V LED

Technical Information

LAMP LIFE	50000 hours
COLOR RENDERING	92 CRI
LAMP COLOR	2700K
LUMENS/WATT	103.29
LUMINOUS FLUX	723 lumens

CLICK TO VIEW PRODUCT

Notes: