


# 1100FTUESEM

6 3/4" Aperture 1 Light, 120V 26/32W Triple Tube Fluorescent Frame-In Kit



Frame-In Kit	Voltage	Lamp	Reflector Trims — See Individual Reflector Trim Specification Sheets							
			Open Downlight						Enclosed Diffusers	Wall Washer
			Reflector	Cone	Satin Cone	Baffles	Basic White	Cross Blade		
1100FTUESEM	120V	26W and 32W Triple Tube	1143	1112	1108	1105	1171	1132	1121	1135
			1144	1112NM	1108NM	1105WH	1170M1		1124	1135WH
			1144CD	1113	1110	1105BNM			1126	1186
			1145	1113BK	1105NM	1128			1186WH	
			1146	1113CD	1176	1134			1195	
			1146CD	1113WH	1176WH	1177SH			1196	
			1113NM	1179M1	1178SH	1190			1196CD	
			1113CDNM	1179WH						
			1113BKNM							

- 1. Mounting Frame:** 0.036" (#20 ga.) galvanized steel. Accommodates all ceilings up to 1" thick; including existing or inaccessible areas. Breakout section and anchor nails for existing ceilings. Push-in/twist-out rotoclips hold reflector flush to ceiling.
- 2. Junction Box:** 0.063" (#14 ga.) 4" x 3 1/2" x 2" galvanized steel. U.L. listed for maximum of 8 No. 12 ga., 75°C through branch circuit conductors. Integral cable clamps permit attachment of nonmetallic Romex® or Armored cable without the need for separate connectors.
- 3. Mounting Bars:** 0.059" (#16 ga.) galvanized steel. 13" long bars extend to 27", rotatable and lockable, with integral T-bar tabs. Attaches to wood joist or T-bar ceilings without need of accessories.
- 4. Socket Housing:** Steel precisely attached to reflector by spring clip.
- 5. Socket:** Four-pin base, molded thermoplastic. Prewired with No. 18 AWM leads to junction box.
- 6. Ballast:** Electronic 120V, end of lamp life protected, FCC class "B" consumer limits, class "A" sound rating. Energy Star® qualified. Insulation must be kept 3" away from fixture sides and wiring compartment and must not be placed above fixture in a manner which will entrap heat.
- 7. Emergency Battery:** 90 minute battery backup, complete with an LED charging indicator light and integrated test switch.

	26W	32W
Input Volts:	<u>120V</u>	<u>120V</u>
Input Watts:	29	36
Amps:	.24	0.31
Minimum starting temperature is 0°F.		

<b>Mounting Bars:</b>	<b>1964</b> - 20" set of (2)
<b>T-Bar Anchor Clips:</b>	<b>1956</b> - set of (4) for use with above bars
<b>Concealed Spine Ceiling Kit:</b>	<b>1965</b> - set of (4), 1 1/2" to 2 1/2" Mtg. Ht.
<b>Plaster Ceiling Ring:</b>	<b>1960</b> - 7/8" depth for wet plaster ceilings.
<b>Extra-Thick Ceiling Mounting Ring:</b>	<b>1967A</b> - up to 2" thick ceilings.

UL (Suitable for Damp Locations), I.B.E.W.

Romex® is a registered trademark of General Cable Industries Inc.

**Job Name:**  
**Cat. No.:**  
**Lamp(s):**  
**Notes:**

**Lightolier** a Genlyte company [www.lightolier.com](http://www.lightolier.com)  
631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710  
We reserve the right to change details of design, materials and finish.  
© 2011 Genlyte Group LLC • D0711

# HIGHTOLLER®