Installation Instruction for


Crystal Galaxy

IMPORTANT INFORMATION


- Please read this installation instructions before start installation.
- Risk of Injury: Make sure that the power to the electrical box is off before starting the installation, or changing the
- The fixture is rated for indoor dry locations only.
- Have a qualified electrician to install this fixture.

SAVE THESE INSTRUCTIONS!

Install the Fixture



1: Determine the overall fixture height by adjusting the aircraft cable going into the canopy. Push the tab on the cord grip to release the aircraft cable.



CAUTION: To reduce risk of a burn or electrical shock during lamping, disconnect the power to the fixture.

Use MAX 2 Watt, Type E10 Miniature Lamp, for each Socket, or **0.3** Watt LED E10.



NOTE: Use a soft cloth and fingers to install the lamp.


- 8: Screw each lamp into the socket.
- 9: Hang each crystal onto the peg in front of the lamp.

ATTENTION: When replacing lamp, make sure power to the fixture is turned off. Remove the crystals near socket and replace the lamp with a new one.



1718 W. Fullerton Ave Chicago, IL 60614 Tel: 866-954-4489 Fax: 773-883-6131 www.lightology.com info@lightology.com





- 2: Connect the transformer black and white wires to the power line hot and neutral wires respectively with wire
- 3: Connect the ground wires based on local electrical
- 4: Place the wires and wire nut connections inside the electrical box and mount the back plate to the electrical box with the two #8-32 screws.
- 5: Feed the "+" and "-" fixture wires through the canopy inlets. Cut the excess wires, leaving 6 inches for power connections.
- **6:** Connect these wires properly to the transformer 12 volt wires with wire nuts.
- 7: Slide the canopy up over the back plate. Align the mounting hole and secure it in place by tightening the screw.

