


◍

#### 0.35 (0.9cm) 0.375' (0.95cm) 0 35" (0.9cm) 0 375 (0.95cm) 1 46' (3.7cm) 0.9 (2.3cm) 0.9' - 0.9" (2.3cm) (2.3cm) R1 D1



# **Description:**

Cirrus Float Center Feed features a direct 1" (D1), rectangular 1" (R1) or a tubular 1 1/8" (T1) lens, offering an array of choices for style, functionality and beam distribution. At 7 watts per foot, the 24VAC suspension contains very warm white 2,700K or warm white 3,000K 92CRI LEDs and is available in lengths from 36" up to 72". Customized lengths available in 2.4" increments. Cirrus Float includes 26" rectangle canopy and feeds power at the center from a 24VAC Class 2 electronic low voltage LED transformer (included), which fits inside a standard 4" electrical box with round plaster ring and is dimmable with an electronic low voltage dimmer. Hardware and supporting cables are Antique Bronze for Antique Bronze and Black fixtures and are Satin Nickel for all other finishes. Power cables are Satin Nickel for all finish options. Fixture is covered by a 5 year warranty.

# Finish:

Satin Aluminum, Satin Nickel, Chrome, Antique Bronze, White and Black; Custom finishes also available.

### **Applications:**

Indoor - Architectural lighting, general lighting and retail.

#### Lamp:

Version	<b>Watts</b> per Foot	<b>Lum</b> per Watt	per Foot	<b>92CRI</b> 27K, 30K	50,000 Hour Lamp Life
D1	7	34	241	•	•
R1	7	36	262	•	•
T1	7	36	268	•	•

Lumen values are based on the 3000K LED test.

# **Power Supply:**

120V input, 24VAC Class 2 output; electronic low voltage LED transformer (included) that fits inside standard junction box

# Dimming

Dimmable with electronic low voltage dimmer. Lutron: Diva #DVELV-300P; Skylark #SELV-300P dimmers recommended

