

CounterAttack Xenon

Linkable Undercabinet Lighting

NCAX-120

FEATURES

- 20V hardwire and portable SpeedLink options
- Warm 120V, 35W Xenon color temperature - 2,900°K
- 9,000-hour lamp life
- Dimmable with standard Incandescent dimmer (must meet minimum load of dimmer)
- Available in five lengths: 8", 16", 24", 32", 40"
- SpeedLink system links a maximum of 600W
- Low profile – only 1½" high
- Linking and non-linking versions available
- On/Off switch
- UL/C-UL listed for damp location



HOUSING / HEAT SINK

- Rolled steel, painted post manufacturing with molded plastic end caps
- Non-yellowing U.V. coated glass prismatic diffuser for maximum light distribution and U.V. protection
- Removable hinged diffuser for east and safe lamp replacement
- Patented cooling system provides longer lamp life than other models
- Repositioned cooling slots
- Trade-sized knockouts on back and top for through-wiring, Wiremold, flex, Romex, or rigid conduit

MOUNTING

- Installs easily with two easy-to-access captive screws
- Knockouts on ends (non-linking only), back and top for through-wiring, Wiremold, flex, Romex or rigid conduit

FINISHES

- Bronze (BZ)
- Stainless Steel (SS)
- White (WT)

NCAX-120-8-BZ



NCAX-120-16-WT




NCAX-120-24-SS



NCAX-120-32-WT



NCAX-120-40-WT



	Length	l x w x h	Lamps	Version
NCAX-120-8-XX	8"	8" x 5" x 1½"	1	Non-Linking
NCAX120-8-XX	8"	8" x 5" x 1½"	1	SpeedLink
NCAX-120-16-XX	16"	16" x 5" x 1½"	2	Non-Linking
NCAX120-16-XX	16"	16" x 5" x 1½"	2	SpeedLink
NCAX-120-24-XX	24"	24" x 5" x 1½"	3	Non-Linking
NCAX120-24-XX	24"	24" x 5" x 1½"	3	SpeedLink
NCAX-120-32-XX	32"	32" x 5" x 1½"	4	Non-Linking
NCAX120-32-XX	32"	32" x 5" x 1½"	4	SpeedLink
NCAX-120-40-XX	40"	40" x 5" x 1½"	5	Non-Linking
NCAX120-40-XX	40"	40" x 5" x 1½"	5	SpeedLink

XX = two digit finish code WHite (WT), Stainless Steel (SS), Bronze (BZ)

Project Notes:



A Division of Troy-CSL

14508 Nelson Avenue City of Industry, CA 91744 Tel 626-336-4511 Fax 626-336-4266 www.cslighting.com

Rev 120915