

# SS3 BBB SOFT STRIP 2.6W, 24VDC HIGH OUTPUT, BLUE ONLY

REV.07.20.15



SS3-24V\_-BBB

**Maximum Length  
Before Refeeding: 36 Feet**

LENGTH IN FEET	TOTAL WATTAGE	LENGTH IN FEET	TOTAL WATTAGE
1	3W	19	50W
2	6W	20	52W
3	8W	21	55W
4	11W	22	58W
5	13W	23	60W
6	16W	24	63W
7	19W	25	65W
8	21W	26	68W
9	24W	27	71W
10	26W	28	73W
11	29W	29	76W
12	32W	30	78W
13	34W	31	81W
14	37W	32	84W
15	39W	33	86W
16	42W	34	89W
17	45W	35	91W
18	47W	36	94W

## Description:

Soft Strip (SS3) BBB provides dynamic color effects with blue LEDs. The 1/2" wide flexible copper strip, with an optically clear protective coating, is sold in 1 ft increments up to 36 ft with easy plug-in connectors on each end. Includes a 8 ft power feed cable. For custom lengths, smaller segments are available in 4 inch increments (sold separately). Use plug-in flexible connectors for making turns and custom configurations. Self-adhering SS3 mounts to most smooth finished surfaces with the industrial strength 3M tape (provided on back of strip); some unfinished surfaces may require screw-in mounting clips (sold separately). Designed for indoor, open-air environments, SS3 includes a flexible aluminum heat sink to extend LED life. Fixtures include 5 year warranty.

## Applications:

Indoor Only - Under/above cabinet, cove lighting or accent toe kicks, behind sheer curtains, step, entertainment, display, night clubs, molding accent, media room

## Lamp:

18 Blue LEDs per foot  
LED lamps consume 2.6 watts per foot

## Average Lamp Life:

32,000 hours

## Power Supply:

**PSB-60W-ELV-24DC** 120VAC input, 60 watt output  
**PSB-96W-010-24VDC** 120-277VAC input, 96 watt output  
**PSB-100W-ELV-24VDC** 120VAC input, 96 watt output  
**PSB-2X96W-010-24VDC** 120-277VAC input, 2x96 watt output  
**PSB-2X100W-ELV-24VDC** 120VAC input, 2x96 watt output

## Mounting Straps & Clips:

### SS-SU

Use U-Strap every 6 to 12 inches for extra support (30 per package).

### SS-ST

Use Tie Strap every 6 to 12 inches for extra support (30 per package).

### SS-MCL

Screw In Mounting Clip mounts beneath strip, snapping the Strip into place for additional support (10 per package).



**SS3-24V-4IN-BBB**  
4 Inch Soft Strip

System	Voltage	Length	Color Temperature
<b>SS3</b>	<b>24V</b>	<b>4IN</b>	<b>BBB</b>
<small>SS3 Soft Strip 2.6W per Ft</small>	<small>24V 24 Volt</small>	<small>4IN 4 Inch</small>	<small>BBB Blue, Blue, &amp; Blue</small>

System	Voltage	Length in Feet	Color Temperature
<b>SS3</b>	<b>24V</b>	<b>36</b>	<b>BBB</b>
<small>SS3 Soft Strip 2.6W per Ft</small>	<small>24V 24 Volt</small>	<small>Sold in 1 ft increments up to 36 ft (Example 36=36')</small>	<small>BBB Blue, Blue, &amp; Blue</small>

PROJECT:

FIXTURE  
TYPE:

DATE:



**Application:** 0-10V dimming for Soft Strip BBB 2.6W-24V

**Power Supply:** 96 watt, 120-277 volt input, 24 volt DC output **PSB-96W-010-24VDC**  
 192 watt, 120-277 volt input, 24 volt DC output **PSB-2X96W-010-24VDC**

**Dimming:** Dimmable with 0-10V Controller using power supply above.  
 Lightolier: ZP600FAM120 is recommended

