# **JUNO**®

Project:

Fixture Type:

Location:

Contact/Phone:

### TRAC-MASTER®

Avant Garde

**MAMBA® SERIES** 

T860, T863 and T868

#### **PRODUCT DESCRIPTION**

Mamba is a strikingly original, front loading gimbal-ring design. Its gracefully curved and tapered elements flow into a gimbal ring that appears to float, while the gently scooped socket housing reinforces a concave/convex theme. Concealed wiring and sleek trac adapter create an ultra-clean appearance.

Mamba uses high-quality, die-cast aluminum construction and is available in attractive white, black and silver finishes.





#### Low Voltage MR16

Construction Die cast aluminum housing.

**Lamp** 12V, 50W maximum MR16 GU5.3/GX5.3 bi-pin • Halogen lamps must be MR16CG type with integral lens (cover glass).


**Socket** Ceramic bi-pin.

**Transformer** Must be ordered separately • Compatible with T537 or T538 12V electronic transformer for halogen lamps (D1.2.1) • Compatible with T537U universal 12V electronic transformer for LED or halogen lamps (D1.2.5) • Compatible with T539 12V electronic transformer for halogen lamps (D1.2.0) • Compatible with T542 or T543 12V magnetic transformer for LED or halogen lamps (D1.2.0).

Labels UL and C-UL Listed.

Product specifications subject to change without notice.

Catalog Number	Finish	Lamp
T860WH	White	50W MR16 max. (halogen must use MR16CG type)
T860BL	Black	50W MR16 max. (halogen must use MR16CG type)
T860SL	Silver	50W MR16 max. (halogen must use MR16CG type)



#### Line Voltage PAR30

**Construction** Die cast aluminum housing.

Lamp 120V, 75W maximum PAR30 medium base.

**Socket** Medium base porcelain with nickel plated copper screw shell.

Adapter Unique, attractive conical-elliptical shaped trac adpter


Copper alloy contacts provide precise spring action – no arcing and will
not take a set • True, positive electrical ground • Spring-loaded positive latch
with embossed polarity arrow secures trac light to trac • "Pull-up" contact to up
position for two-circuit application • Polarity indicator embossed on
copper contact.

Aiming 360° horizontal rotation • 90° vertical aiming capability.

Labels UL and C-UL Listed.

Product specifications subject to change without notice.

Catalog Number	Finish	Lamp
T863WH	White	75W PAR30 max.
T863BL	Black	75W PAR30 max.
T863SL	Silver	75W PAR30 max.





## **TRAC-MASTER®**

Avant Garde

### MAMBA® SERIES

T860, T863 and T868

### Line Voltage PAR38

Construction Die cast aluminum housing.

Lamp 120V, 150W maximum PAR38 medium base.

**Socket** Medium base porcelain with nickel plated copper screw shell.

Adapter Unique, attractive conical-elliptical shaped trac adpter • Copper alloy contacts provide precise spring action – no arcing and will not take a set • True, positive electrical ground • Spring-loaded positive latch with embossed polarity arrow secures trac light to trac • "Pull-up" contact to up position for two-circuit application • Polarity indicator embossed on copper contact.

Aiming 360° horizontal rotation • 90° vertical aiming capability.

Labels UL and C-UL Listed.

Product specifications subject to change without notice.

Catalog Number	Finish	Lamp
T868WH	White	150W PAR38 max.
T868BL	Black	150W PAR38 max.
T868SL	Silver	150W PAR38 max.

