



# TRAC-MASTER®

Classics

## THEATRICAL LIGHTS

### T290 and T295

Project: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Location: \_\_\_\_\_

Contact/Phone: \_\_\_\_\_

#### PRODUCT DESCRIPTION

Theatrical Lights are designed for applications requiring controlled light, higher intensities and wattages.

**Construction** Vented steel housing.

**Labels** UL listed, CSA certified.

Product specifications subject to change without notice.

#### Low Voltage MR16

**Lamp** 12V, 75W maximum MR16 GU5.3/GX5.3 bi-pin.

**Socket** Ceramic bi-pin with integral heat shield.

**Aiming** 90° vertical aiming capability and 358° rotation

- One locking knob provided.



**Transformer** Must be ordered separately • Compatible with T537 or T538 12V electronic transformer for halogen lamps (D1.2.1) • Compatible with T537U universal 12V electronic transformer for LED or halogen lamps (D1.2.5) • Compatible with T539 12V electronic transformer for halogen lamps (D1.2.0) • Compatible with T542 or T543 12V magnetic transformer for LED or halogen lamps (D1.2.0).

Catalog Number	Finish	Lamp
T290BL	Black/Black Barn Doors	75W MR16 max.

#### ACCESSORIES

Cat. No.	Description	Cat. No.	Description	Cat. No.	Description
T551-5	Color Filters	T557	Prismatic Spread Lens	T559	Linear Spread Lens
T5501-18	Dichroic Filters	T5520	Diffusion Lens	T5521	Uniformity Lens
T5522	UV Filter	T5559BL	Hexcell Louver	T561-6	Color Filters
T569BL	Cube Cell Louver	T5677	Prismatic Spread Lens	T5678	Linear Spread Lens
T5621	Uniformity Lens	T5622	UV Filter	T5618	Color Correction Filter

T290 can accept one 1 3/4" filter, lens or louver in place of clear glass supplied with MR16 fixtures; in addition, the integral barn doors can also accept one 3 3/4" filter, lens or louver.



#### Line Voltage PAR/R20

**Lamp** 120V, 50W maximum R20 or PAR20 medium base.

**Socket** Medium base porcelain with nickel plated copper screw shell.

**Aiming** 90° vertical aiming capability and 358° rotation

- One locking knob provided.

**Adapter** Copper alloy contacts provide precise spring action - no arcing and will not take a set • True, positive electrical ground • On/off switch included • Patented embossed polarity arrows on bottom of adapter • Spring-loaded positive latch with embossed polarity arrows secures trac light to trac • "Pull-up" contact to up position for two-circuit application.

Catalog Number	Finish	Lamp
T295BL	Black/Black Barn Doors	50W R20 or 50W PAR20 max.

#### ACCESSORIES

Cat. No.	Description	Cat. No.	Description	Cat. No.	Description
T561-6	Color Filters	T569BL	Cube Cell Louver	T5677	Prismatic Spread Lens
T5678	Linear Spread Lens	T5621	Uniformity Lens	T5622	UV Filter
T5618	Color Correction Filter				

