



Complete Fixture consists of Reflector Trim & Frame-In Kit. Select each separately.

| Reflector Trim | | Frame-In Kit — See Individual Frame-In Kit Specification Sheets | | | |
|----------------|--------------|---|------------------------------------|--------------|--------|
| Low Voltage | | | | | |
| | Frame-In Kit | Installation Type | Lamping | Height | |
| 2026WH | Matte White | 2000LV | Standard Non-IC | 20W-50W MR16 | 5 7/8" |
| | | 2000LVR | Remodeler Non-IC | 37W MR16 | 5 7/8" |
| | | 2000LVRE1 | Remodeler Non-IC | 37W MR16 | 5 7/8" |
| | | 2000LVE1 | Electronic Low Voltage Non-IC 120V | 20W-50W MR16 | 5 7/8" |
| | | 2000LVE2 | Electronic Low Voltage Non-IC 277V | 20W-50W MR16 | 5 7/8" |
| | | 2004ICV/N | Lyte ^{ning} AirSeal® IC | 20W-50W MR16 | 7 1/4" |
| | | 2000LVNT | Non-IC (no transformer) | 20W-42W MR16 | 5 7/8" |

Features

- Housing:** Galvanized Steel, .026" thick (22 ga.).
- Trim Flange:** Die-cast aluminum .060" thick.
- Frame-In Kit:** (2000LV standard frame shown) Other frames shown on the right. See Frame-In Kit specification sheets for more details.
- Glass:** Frosted Glass Diffuser

Options & Accessories

Retaining Clips: 1955 - For Installing in Existing Ceiling

Labels

UL (Suitable for Wet Locations - Covered Ceiling)

Job Information

Type:

Job Name:

Cat. No.:

Lamp(s):

Notes: