

Complete Fixture consists of Reflector Trim & Frame-In Kit. Select each separately.

Reflector Trim	Frame-In Kit — See Individual Frame-In Kit Specification Sheets  LED				
	Frame-In Kit	Installation Type	Lamping	Height	
1090	1001LED 1001LEDEM 1000LEDREM	Non-IC Non-IC EM Non-IC Remodeler Non-IC Retrofit	LED LED LED LED	5 1/4" 5 1/4" 5 1/4" 5 1/4"	
	Incandescent			Incandescent	
	Frame-In Kit	Ceiling Type	Lamping	Height	
	1002P1 1003R	Non-IC Non-IC Remodeler	75W PAR30L	5 1/4" 5 1/4"	
	1000IC 1000AICM 1004ICX/N	IC AirSeal® IC AirSeal® IC	60W PAR30S	7 5/16" 7 5/16" 7 1/4"	
	1004IC/N 1004ICR	Non-IC Non-IC Remodeler	75W PAR30S	7 1/2" 7 1/2"	

## **Features**

- 1. Housing: Hydroformed aluminum, .040 thick. min. Non-yellowing, gloss white powder coat finish for permanent reflectivity and surface protection.
- 2. Trim Flange: Frosted clear polycarbonate flange ring. Pull down and release for toolless relamping.
- 3. Frame-In Kit: (1002PI standard frame shown) Other frames noted. See Frame-In Kit specification sheets for more details.
- 4. Glass: Pressed borosilicate glass textured diffuser. Smooth surface on exposed side for wipe down cleaning. Meets NEC® requirements for spas and hot tubs. May be installed less than 7' 6" above max water surface height.

## Labels

UL (Suitable for Wet Locations - Covered Ceilings only), I.B.E.W.

NEC® is a registered trademark of the National Fire Protection Association.

Job Information	Туре:
Job Name:	
Cat. No.:	
Lamp(s):	
Notes:	

Lightolier a Genlyte company www.lightolier.com 631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710 We reserve the right to change details of design, materials and finish. © 2011 Genlyte Group LLC • G0711